

ISO-200

Ground Loop Isolator + Signal Converter



Model: ISO-200



DON'T LET ANNOYING HUM NOISE DRAG YOUR AUDIO SYSTEM DOWN

Expanding on Earthquake's line of audio problem solving products; the new ISO-200 is the leading ground loop isolator and signal converter on the market. The standard A/V receiver output is 600Ω yet most ground loop isolators on the market today have 200Ω at best. When using these substandard products, your A/V receiver has to deliver 3X more current and or compromise the output level. The new ISO-200 comes with an impedance of 600Ω right out of the box matching that of the industry standard. Unlike other products on the market, Earthquake's ISO-200 is constructed with high-quality components and will not roll-off the low frequency response due to undersized transformers resulting in substandard performance. It was designed to kill off the dreaded buzz noise or ground loop while

maintaining high-quality sound from your audio system. The ISO-200 is unique because it not only serves as a ground loop isolator, but it is also a 2-way signal converter. It will convert an unbalanced consumer level RCA signal to a balanced professional level XLR signal and vice versa. The compact and rugged construction of the ISO-200 allows for it to fit into virtually any audio system, and can be mounted to any surface with its built-in mounting bracket. This will give you a cleaner looking install and allow it to be hidden out of sight. When it comes to audio noise and hum issues, Earthquake Sound offers great problem solving solutions for audio professionals and installers to the everyday home and car audio enthusiast.

FEATURES

ISO-200

- Ground loop isolator + signal converter
- XLR for balanced inputs and outputs
- RCA for unbalanced inputs and outputs
- 600Ω impedance industry standard
- Compact rugged construction

MSRP

\$45.00/PIECE

SPECIFICATIONS

Height	3.32" (84.33mm)
Width	2.91" (74.00mm)
Depth	1.35" (34.26mm)
Impedance	600Ω

GLI-200

Ground Loop Isolator



[Model: GLI-200](#)



DON'T LET ANNOYING HUM NOISE DRAG YOUR AUDIO SYSTEM DOWN

Expanding on Earthquake's line of audio problem solving products; the new GLI-200 is the leading ground loop isolator on the market. The standard A/V receiver output is 600Ω yet most ground loop isolators on the market today have 200Ω at best. When using these substandard products, your A/V receiver has to deliver 3X more current and or compromise the output level. The new GLI-200 comes with an impedance of 600Ω right out of the box matching that of the industry standard. Unlike other products on the market, Earthquake's GLI-200 is constructed with high-quality components and will not roll-off the low frequency response due to undersized trans-

formers resulting in substandard performance. It was designed to kill off the dreaded buzz noise or ground loop while maintaining high-quality sound from your audio system. The compact and rugged construction of the GLI-200 allows for it to fit into virtually any audio system, and can be mounted to any surface with its built-in mounting bracket. This will give you a cleaner looking install and allow it to be hidden out of sight. When it comes to audio noise and hum issues, Earthquake Sound offers great problem solving solutions for audio professionals and installers to the everyday home and car audio enthusiast.

FEATURES

GLI-200

- Ground loop isolator
- RCA inputs and outputs
- Signal noise eliminator
- 600Ω impedance industry standard
- Compact rugged construction

MSRP

\$45.00/PIECE

SPECIFICATIONS

Height	2.85" (72.49mm)
Width	3.32" (84.45mm)
Depth	1.35" (34.33mm)
Impedance	600Ω